

MARK DATE





design and information shown on this drawing is provided a service to the project owner, engineer and contractor by stech Engineered Solutions LLC ("Contech"). Neither this					OWNITEON	10		
wing, nor any part thereof, may be used, reproduced or dified in any manner without the prior written consent of					C SNTECH			
tech. Failure to comply is done at the user's own risk and tech expressly disclaims any liability or responsibility for h use.					ENGINEERED SOLUTIONS LLC			
iscrepancies between the supplied information upon which					A QUIKRETE' COMPANY			
drawing is based and actual field conditions are encountered site work progresses, these discrepancies must be reported					19060 Cr 66 Greeley, CO 80631			
Contech immediately for re-evaluation of the design. Contech epts no liability for designs based on missing, incomplete or		DATE	DEVISION DESCRIPTION	D)/	800-328-2047 320-345-9126 320-566-3	3148 FAX		

REVISION DESCRIPTION



OPHINE	1111				
PROJECT No.:	SEQ.	No.:	E:		
830834	0.	10	3/3/2025		
DESIGNED:		DRAWN:			
DBA			K	BK	
CHECKED:		APPR	OVE	D:	
DBA			S	SLJ	
SHEET NO.:					
	1	OI	F	9	

GENERAL NOTES

- CONTECH ENGINEERED SOLUTIONS IS RESPONSIBLE FOR THE DESIGN AND SHOP FABRICATION OF THE BRIDGE STRUCTURE ONLY. ALL MEANS, METHODS, AND EQUIPMENT USED FOR FIELD ASSEMBLY AND INSTALLATION OF THE BRIDGE STRUCTURE, INCLUDING PREPARATION OR REVIEW AND APPROVAL OF PROJECT SPECIFIC ERECTION PLANS, ARE OUTSIDE OF CONTECH'S RESPONSIBILITY.
- 2. DESIGN IS IN ACCORDANCE WITH THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, 8th EDITION 2017 WITH CA AMENDMENTS
- 3. MATERIALS (UNLESS NOTED OTHERWISE)
 - a. STRUCTURAL STEEL: ASTM A709 GRADE 50 W WEATHERING STEEL
 - b. STRUCTURAL BOLTS: ASTM F3125 GRADE A325 TYPE 3
 - c. ELASTOMERIC PADS: GRADE 4, 55 DUROMETER
 - d. BRIDGE RAIL/CURB: AASHTO M180 TYP I OR II GALV.
 - e. BRIDGE RAIL BOLTS: AASHTO M180 GALV.
- 4. DESIGN BASED ON LOAD COMBINATIONS OF THE FOLLOWING LOADS:
 - a. BRIDGE DEAD LOAD
 - b. FUTURE WEARING SURFACE OF 35 PSF
 - c. VEHICLE LIVE LOAD:
 - DESIGN VEHICLE: HL-93, ADTT = 20, LL DEFLECTION LIMIT = L/500
 - OWNER SPECIFIED VEHICLE: P15
 - d. WIND LOADING PER AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS SECTION 3.8:
 - WIND SPEED = 110 MPH
 - WIND EXPOSURE CATEGORY = C
 - MAX HEIGHT OF STRUCTURE = 33 FT
 - e. SEISMIC LOADING PER CALTRANS SEISMIC DESIGN SPECIFICATIONS FOR STEEL BRIDGES, 2ND ED. AND CALTRANS ARS ONLINE TOOL. TRANSVERSE LOADS CALCULATED USING THE TRANSVERSE PERIOD OF THE BRIDGE AND LONGITUDINAL LOADS CALCULATED USING A PERIOD OF ZERO. A RESPONSE MODIFICATION FACTOR OF 1.0 IS USED FOR THE CALCULATION OF BEARING REACTIONS. IT SHALL BE THE RESPONSIBILITY OF THE FOUNDATION ENGINEER TO DETERMINE THE FORCES USED FOR THE FOUNDATION DESIGN. SEISMIC PARAMETERS USED ARE AS FOLLOWS:
 - SITE CLASS: C
 - LATITUDE = 38.4882
 - LONGITUDE = -122.4864
 - TRANSVERSE PERIOD OF BRIDGE = Tm = 0.031 SEC

MARK

DATE

- 5. BRIDGE RAIL DESIGNED FOR TL-2 LOADING IN ACCORDANCE WITH AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS APPENDIX A13.2 (RAIL HAS NOT BEEN CRASH TESTED)
- 6. BRIDGE STRUCTURE SHALL BE SHOP FABRICATED IN ACCORDANCE WITH AWS D1.5.
- 7. ALL SHOP WELDING SHALL USE THE GAS METAL ARC WELDING OR FLUX CORED ARC WELDING PROCESS
- 8. CLEANING: ALL EXPOSED SURFACES OF STEEL TO BE CLEANED IN ACCORDANCE WITH STEEL STRUCTURES PAINTING COUNCIL SURFACE PREPARATION SPECIFICATIONS NO. 7, SSPC-SP7 BRUSH-OFF BLAST CLEANING. EXPOSED SURFACES OF STEEL SHALL BE DEFINED AS THOSE SURFACES SEEN FROM THE DECK OR FROM THE OUTSIDE OF THE STRUCTURE. ALL OTHER SURFACES TO HAVE STANDARD MILL FINISH.
- 9. ALL STRUCTURAL BOLTED CONNECTIONS ARE TO BE PRETENSIONED CONNECTIONS. ALL BOLTS ARE TO BE PRETENSIONED PER THE REQUIREMENTS OF SECTION 8.2 OF THE SPECIFICATION FOR STRUCTURAL JOINTS USING HIGH-STRENGTH BOLTS BY RCSC.
- 10. ALL FIELD INSTALLED BOLTS, NUTS AND WASHERS SHALL BE FURNISHED IN THE AMOUNT OF 5% IN EXCESS OF THE NUMBER REQUIRED FOR EACH SIZE AND LENGTH. IF FIELD INSTALLED BOLTS DO NOT SMOOTHLY ENGAGE UP TO SNUG-TIGHT, THERE MAY BE AN OBSTRUCTION WITHIN THE THREADS, THE BOLTS SHOULD BE REMOVED, THE THREADS ON THE BOLT AND NUT CLEANED AND RETAPPED IF NECESSARY TO ALLOW SMOOTH INSTALLATION OF THE BOLT.
- 11. MAINTENANCE NOTE: CONTECH ENGINEERED SOLUTIONS RECOMMENDS NOT APPLYING DE-ICING OR DUST PROHIBITIVE CHEMICALS OR SALTS TO ANY PART OF THE BRIDGE STRUCTURE. IF DE-ICING OR DUST PROHIBITIVE CHEMICALS OR SALTS ARE APPLIED TO ANY PART OF THE BRIDGE STRUCTURE, CONTECH ENGINEERED SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY RESULTANT ACCELERATED CORROSION.
- 12. SURFACE WATER DRAINAGE OFF OF THE BRIDGE DECK IS NOT THE RESPONSIBILITY OF CONTECH ENGINEERED SOLUTIONS. IF DECK DRAINS OR ANY OTHER MODIFICATIONS TO THE DECK SYSTEM ARE NEEDED FOR DECK DRAINAGE, THEY MAY BE ADDED, HOWEVER THE DETAILS MUST BE APPROVED BY CONTECH ENGINEERED SOLUTIONS PRIOR TO THE MODIFICATIONS BEING MADE.

CONCRETE DECK NOTES:

- 1) CONTECH ENGINEERED SOLUTIONS IS RESPONSIBLE FOR THE STRUCTURAL DESIGN OF THE CONCRETE DECK. ALL ISSUES RELATED TO MATERIAL SUPPLY, TESTING, AND INSTALLATION, INCLUDING REVIEW AND APPROVAL OF MIX DESIGNS AND REINFORCING SHOP PLANS, ARE OUTSIDE OF CONTECH'S RESPONSIBILITY.
- 2) CONCRETE MIX DESIGN, MATERIALS, MIXING, PLACEMENT, FINISHING AND TESTING SHALL BE IN ACCORDANCE WITH THE PROJECT CONTRACT DOCUMENTS. IF THESE ITEMS ARE NOT COVERED IN THE PROJECT CONTRACT DOCUMENTS THE REQUIREMENTS OF SECTION 552 OF FEDERAL HIGHWAY ADMINISTRATION STANDARD SPECIFICATIONS FOR CONSTRUCTION OF ROADS AND BRIDGES ON FEDERAL HIGHWAY PROJECTS (FP-14) SHALL BE USED. FP-14 CAN BE VIEWED OR DOWNLOADED AT: https://highways.dot.gov/federal-lands/specs
- 3) MINIMUM MATERIAL REQUIREMENTS:
- a) CONCRETE
- i) STRENGTH (f'c) = 4500 PS
- ii) AIR CONTENT OF 6% +/- 1.5%
- iii) UNIT WEIGHT OF 145 PCF MAX
- b) REINFORCING STEEL: ASTM A615 OR AASHTO M31 GRADE 60
- 4) THE USE OF EPOXY COATED REBAR, GALVANIZED REBAR, DECK SEALERS OR ANY OTHER FORM OF PROTECTION OF THE REBAR SHALL BE DONE AS NEEDED FOR LOCAL CONDITIONS OR AS REQUIRED PER THE PROJECT CONTRACT DOCUMENTS AND IS NOT THE RESPONSIBILITY OF CONTECH ENGINEERED SOLUTIONS.
- 5) THE CONTRACTOR MUST EXERCISE CARE TO CONTROL TRAFFIC AND STORAGE OF MATERIALS ON THE FORM DECK BEFORE CONCRETE IS PLACED.
- 6) REINFORCING BARS MAY BE SPLICED IF REQUIRED. SPLICES SHALL BE STAGGERED EVERY OTHER BAR. TRANSVERSE BAR SPLICES SHALL BE LOCATED AT OR NEAR THE 1/3 POINTS BETWEEN GIRDERS. REQUIRED SPLICE LENGTHS ARE AS FOLLOWS:

BAR	MINIMUM LAP
TOP TRANSVERSE #5 BARS	27"
BOTTOM TRANSVERSE #5 BARS	34"
TOP LONGITUDINAL #4 BARS	22"
BOTTOM LONGITUDINAL #5 BARS	27"

QUALITY ASSURANCE NOTES

- 1. BRIDGE STRUCTURE SHALL BE INSPECTED IN ACCORDANCE WITH AWS D1.5 AND CONTECH'S QUALITY MANUAL. ADDITIONAL INSPECTIONS, INCLUDING FIELD, AND ANY SPECIAL INSPECTIONS, ARE OUTSIDE OF CONTECH'S RESPONSIBILITY.
- 2. BRIDGE SHALL BE BUILT IN AN AISC CERTIFIED SHOP. THE SHOP SHALL HAVE UP TO DATE QUALITY CERTIFICATION BY AISC AS CERTIFIED BRIDGE FABRICATOR ADVANCED
- 3. AT LEAST ONE CERTIFIED WELD INSPECTOR (CWI) QUALIFIED TO AWS QC1, SHALL BE PRESENT DURING THE COMPLETE FABRICATION OF THE BRIDGE. THE CWI SHALL PROVIDE WRITTEN DOCUMENTATION THAT THE BRIDGE HAS BEEN FABRICATED IN ACCORDANCE WITH THE APPROVED DRAWINGS.
- 4. WELD PROCEDURE SPECIFICATIONS (WPS) AND ASSOCIATED PROCEDURE QUALIFICATION RECORDS (PQR) AND WELDER QUALIFICATION TEST RECORDS (WQTR) MAY BE REQUIRED TO BE SUBMITTED.
- 5. MATERIAL CERTIFICATIONS SHALL BE AVAILABLE FOR REVIEW FOR ALL MATERIALS WITHIN THE BRIDGE, INCLUDING ROTATIONAL CAPACITY TEST FOR ALL STRUCTURAL BOLTS. TRACEABILITY OF HEAT NUMBERS IS REQUIRED FOR ALL STEEL. CHARPY V-NOTCH TESTING FOR ZONE 2 SHALL BE REQUIRED ON GIRDER MATERIALS.
- 6. DOCUMENTATION SHOWING THE PERFORMANCE OF ALL CRITICAL QUALITY CHECKS SHALL BE MADE AVAILABLE FOR REVIEW IF REQUESTED.
- 7. ALL STRUCTURAL STEEL SHALL MEET THE BUY AMERICA REQUIREMENTS PER CFR 635
- 8. THIRD PARTY INSPECTION MAY BE REQUIRED.





design and information shown on this drawing is provided service to the project owner, engineer and contractor by tech Engineered Solutions LLC ("Contect"). Neither this ving, nor any part thereof, may be used, reproduced or iffed in any manner without the prior written consent of			
			CINIE
tech. Failure to comply is done at the user's own risk and tech expressly disclaims any liability or responsibility for n use.			ENGINEERED SOLU
. 400.			1

REVISION DESCRIPTION

A QUIKRETE COMPANY

19060 Cr 66 Greeley, CO 80631

CONTECH
CONTRACT


320-345-9126 320-566-3148 FAX


800-328-2047




BIGR

- Control					
PROJECT No.:	SEQ.	SEQ. No.:		TE:	
830834	0.	10	3	3/3/2025	
DESIGNED:		DRAW	/N:		
DBA			K	BK	
CHECKED:		APPR	OVE	D:	
DBA			SLJ		
SHEET NO.:				,	
	2	OI	F	9	







*NOTE:
ANCHOR BOLTS ARE DESIGNED BY CONTECH FOR STEEL STRENGTH IN SHEAR
AND TENSION OF THE ANCHOR BOLT ONLY. ALL DESIGN CONSIDERATIONS
REGARDING CONCRETE BREAKOUT STRENGTH IN SHEAR AND TENSION,
PULLOUT STRENGTH, CONCRETE SIDE-FACE BLOWOUT STRENGTH, CONCRETE
PRYOUT STRENGTH, EMBEDMENT DEPTH, TYPE OF ANCHORAGE OR ANY OTHER
CONCRETE FAILURE MODES ARE NOT CONSIDERED AND ARE NOT THE
RESPONSIBILITY OF CONTECH. IF LARGER DIAMETER BOLTS ARE REQUIRED TO
MEET ANY OF THESE REQUIREMENTS, THAT INFORMATION MUST BE PROVIDED
TO CONTECH PRIOR TO BEGINNING ANY FABRICATION ON THE BRIDGE. IT SHALL
BE THE RESPONSIBILITY OF THE FOUNDATION ENGINEER TO DETERMINE THE
SEISMIC CONNECTION FORCES IN ACCORDANCE WITH GENERAL NOTE 2.

UNFACTORED BEARING	UNFACTORED BEARING		INTERIOR	GIRDER	MAX AT EXTERIOR GIRDER			TOTAL AT BRIDGE END		
REACTIONS IN KIPS		Р	Т	L	Р	Т	L	Р	Т	L
DEAD LOAD (DC)		27.22	_	_	20.64	_	_	95.72	_	ı
WEARING SURFACE & UTILITES	(DW)	5.44	-	_	5.44	_	_	21.78	_	ı
HL-93 DESIGN VEHICLE	(LL)	55.89	-	_	48.67	_	_	153.29	_	ı
HL-93 DESIGN VEHICLE	(LL+IM)	70.21	_	_	61.14	_	_	192.54	_	1
P15 OWNER SPECIFIED VEHICLE	(LL)	78.51	_	_	68.36	_	_	107.65	_	-
F 13 OWNER SPECIFIED VEHICLE	(LL+IM)	98.13	-	_	85.46	_	_	134.56	_	1
WIND LOAD (WS)		-12.41*	2.05	_	0.00*	2.05	_	-12.41*	8.21	1
THERMAL LOAD (TU)		_	_	4.14	_	_	4.14	_	_	16.56
BRAKING FORCE (BR)		_	_	9.00	_	_	9.00	_	_	36.00
SEISMIC LOAD (EQ)		_	24.89	38.19	_	24.89	38.19	_	99.57	152.75

LIFTING WEIGHTS IN LBS								
ITEM	QTY	UNIT WEIGHT	TOTAL WEIGHT					
BRIDGE MODULE 1 ASSEMBLY	1	13,040	13,040					
BRIDGE MODULE 2 ASSEMBLY	1	13,040	13,040					
LOOSE ITEMS	LS	-	7,280					
		TOTAL BRIDGE WEIGHT:	33,360					





VE/83	The design and information shown on this drawing is provided as a service to the project owner, engineer and contractor by Contech Engineered Solutions LLC ("Contech"). Neither this					
٦ ۲	drawing, nor any part thereof, may be used, reproduced or modified in any manner without the prior written consent of					
JEC.	Contech. Failure to comply is done at the user's own risk and Contech expressly disclaims any liability or responsibility for such use.					
וואאר	If discrepancies between the supplied information upon which					
HA L	the drawing is based and actual field conditions are encountered as site work progresses, these discrepancies must be reported to Contech immediately for re-evaluation of the design. Contech] -
2	to Contech immediately for re-evaluation of the design. Contech accepts no liability for designs based on missing, incomplete or inaccurate information supplied by others.	MARK	DATE	REVISION DESCRIPTION	BY	ا ا

ENGINEERED SOLUTIONS LLC


A QUIKRETE' COMPANY


19060 Cr 66 Greeley, CO 80631


800-328-2047 320-345-9126 320-566-3148 FAX




OPHINE	1925			
PROJECT No.:	SEQ.	No.:	DATE	::
830834	0.	010		3/2025
DESIGNED:		DRAW	N:	
DBA			KE	3K
CHECKED:		APPR	DOVED	:
DBA			SI	_J
SHEET NO.:				
	3	OI	=	9









C 79360

PROFESSIONAL LEE JOHN OF CALLED 3/3/25

 $\underline{\mathsf{THRIE}\text{-}\mathsf{BEAM}\;\mathsf{RAIL}\;\mathsf{ATTACHMENT}\;\mathsf{DETAIL}}$

(W 8x18 POSTS)

REVISION DESCRIPTION

MARK DATE

CENTECH'
ENGINEERED SOLUTIONS LLC

A QUIKRETT COMPANY

19060 Cr 66 Greeley, CO 80631


800-328-2047 320-345-9126 320-566-3148 FAX




54'-9" x 22'-8" SULPHUR CREEK BRIDGE ROLLED GIRDER - SITE-SPECIFIC MODULAR NAPA COUNTY, CA

O WALL	1921				
PROJECT No.:	SEQ.	No.:	DATE:		
830834	0.	10	3/3/2	2025	
DESIGNED:		DRAWN:			
DBA			KBK		
CHECKED:		APPR	OVED:		
DBA			SLJ		
SHEET NO.:					
	5	OI	<u> </u>)	


SCERTIFIED A FABRICATOR







TAPERED BEARING PLATE DETAIL (FIXED)

(SHIPS LOOSE) (QTY: 4)



TAPERED BEARING PLATE DETAIL (EXPANSION) (SHIPS LOOSE) (QTY: 4)









The design and information shown on this drawing is provided as a service to the project owner, engineer and contractor by					Γ
Contech Engineered Solutions LLC ("Contech"). Neither this drawing, nor any part thereof, may be used, reproduced or modified in any manner without the prior written consent of					İ
Contech. Failure to comply is done at the user's own risk and Contech expressly disclaims any liability or responsibility for such use.					
If discrepancies between the supplied information upon which the drawing is based and actual field conditions are encountered]
as site work progresses, these discrepancies must be reported to Contech immediately for re-evaluation of the design. Contech					J,
accepts no liability for designs based on missing, incomplete or inaccurate information supplied by others.	MARK	DATE	REVISION DESCRIPTION	BY	l

TYP 1/8 1 1/2 - 12


END ANGLE

ENGINEERED SOLUTIONS LLC A QUIKRETE' COMPANY

19060 Cr 66 Greeley, CO 80631 800-328-2047 320-345-9126 320-566-3148 FAX



PROJECT No.:	SEQ.	No.:	DATE:					
830834	0.	10	3/3/2025					
DESIGNED:		DRAW	VN:					
DBA			KBK					
CHECKED:		APPR	ROVED:					
DBA			SLJ					
SHEET NO.:								
	6	OI	ı 9					



800-328-2047 320-345-9126 320-566-3148 FAX

MARK DATE

REVISION DESCRIPTION

SULPHUR CREEK BRIDGE **ROLLED GIRDER - SITE-SPECIFIC MODULAR** NAPA COUNTY, CA

L 4x4x3/8

(SHIPS LOOSE)


15/16"Ø HOLES

GIRDER 3

830834 010 SLJ OF


SCERTIFIED FABRICATOR

END DIAPHRAGM ATT. PLATE & SIP ANGLE DETAIL



REVISION DESCRIPTION

BY



C 79360

C 79360

C 79360

C 79360

C 79360



DIAPHRAGM ATT. PLATE & SIP ANGLE DETAIL

The design and information shown on this drawing is provide as a service to the project owner, engineer and contractor by Contech Engineered Solutions LLC ("Contech"). Neither this drawing, nor any part thereof, may be used, reproduced or modified in any manner without the prior written consent of Contech. Failure to comply is done at the user's own risk and Contech expressly disclaims any liability or responsibility for such use.

	such use.		
Į,	If discrepancies between the supplied information upon which		
Ž	the drawing is based and actual field conditions are encountered as site work progresses, these discrepancies must be reported to Contech immediately for re-evaluation of the design. Contech		
2	accepts no liability for designs based on missing, incomplete or inaccurate information supplied by others.	MARK	DATE



A QUIRRETE' COMPANY


19060 Cr 66 Greeley, CO 80631

800-328-2047 320-345-9126 320-566-3148 FAX




54'-9" x 22'-8"						
SULPHUR CREEK BRIDGE						
ROLLED GIRDER - SITE-SPECIFIC MODULAR						
NAPA COUNTY, CA						

PROJECT No.:	SEQ. No.:		DATE:				
830834	010		3/3/2025				
DESIGNED:		DRAWN:					
DBA		KBK					
CHECKED:		APPROVED:					
DBA			S	LJ			
SHEET NO.:							
	8	0	F	9			



GIRDER SHEAR STUD LAYOUT (TYPICAL ALL GIRDERS)

SCREED ELEVATIONS (ELEVATION											
BEFORE DL DEFLECTION) (FT)	BD	1/10	2/10	3/10	4/10	5/10	6/10	7/10	8/10	9/10	ED
LEFT EDGE OF DECK ELEV.	314.788	315.225	315.679	316.152	316.638	317.109	317.550	317.951	318.309	318.624	318.895
LEFT CURBLINE ELEV.	314.802	315.238	315.693	316.165	316.651	317.122	317.563	317.965	318.323	318.637	318.909
"SC" LINE ELEV.	315.022	315.458	315.913	316.385	316.871	317.342	317.783	318.185	318.543	318.857	319.129
RIGHT EDGE OF DECK ELEV.	315.242	315.678	316.133	316.605	317.091	317.562	318.003	318.405	318.763	319.077	319.349



1) END DAM NOT SHOWN FOR CLARITY.

2) STAY-IN-PLACE DECK PANS TO BE ATTACHED TO THE SUPPORT ANGLE WITH SELF-TAPPING TEK SCREWS PLACED AT THE FOUR PAN CORNERS AND AT THE 1/3 POINTS ALONG THE LONGITUDINAL OVERLAPS. (4 PER SHEET).

TYPICAL STAY-IN-PLACE DECK MOUNTING DETAIL





The design and information shown on this drawing is provided as a service to the project owner, engineer and contractor by Contech Engineered Solutions LLC ("Contech"). Neither this					Γ
drawing, nor any part thereof, may be used, reproduced or modified in any manner without the prior written consent of					
Contech. Failure to comply is done at the user's own risk and Contech expressly disclaims any liability or responsibility for such use.					ı
If discrepancies between the supplied information upon which the drawing is based and actual field conditions are encountered					ı
as site work progresses, these discrepancies must be reported to Contech immediately for re-evaluation of the design. Contech					
accepts no liability for designs based on missing, incomplete or inaccurate information supplied by others.	MARK	DATE	REVISION DESCRIPTION	BY	ı

ENGINEERED SOLUTIONS LLC A QUIKRETE' COMPANY

19060 Cr 66 Greeley, CO 80631

BIGR CONTRACT 800-328-2047 320-345-9126 320-566-3148 FAX

Control All								
PROJECT No.:	SEQ.	No.:	DATE:					
830834	0.	10	3/3/2025					
DESIGNED:		DRAW	/N:					
DBA			KBK					
CHECKED:		APPR	OVED:					
DBA			SLJ					
SHEET NO.:								
	9	OI	= 9					